



- Integrated water meter and regeneration controller
- Low maintainace costs
- High quality industrial units
- Efficient operation

Water Softeners Bimatic Series

Bimatic water softeners are a range of high quality industrial units that utilise a brass multiport control valve to efficiently produce soft water for any industrial or process application.

The integrated water meter and regeneration controller ensures the availability of softened water at all times due to the duty/standby mode of operation.

Bimatic water softeners are affordable, durable and require low maintenance.

TECHNICAL INFORMATION

BiMatic flow rates

Ranges from 520 to 4,000 l/h depending upon model.

Configuration

Duplex duty/standby mode for continuous soft water delivery. Meter controlled regeneration initiation.

Pipework connections

1" BSPF.

Electrical requirements

230 V, 50 Hz. Power consumption normally 5 - 10w.

Feed water pressure requirements

Minimum 2 bar, maximum 7 bar at inlet during service.

Maximum water temperature

40°C at inlet.

Control valve

Brass multiport valve with teflon coated brass piston on first tank, connected to second tank by stainless steel high pressure tube and brass adaptor.

Water meter in soft water flow directly connected to the drive assembly and controller incorporating switch over programme and hard water blending valve.

Resin vessel

Polyethylene inner liner with glass-fibre reinforced epoxy wound outer shell. Tested to 11 bar.

Food grade high capacity softening resin.

Brine tank

Rigid polyethylene tank with cover and brine collecting chamber housing, with float-operated brine safety valve and automatic air eliminator.

Hardness test kit

For checking softened water quality.

PRODUCT RANGE

Type	Maximum flow rate	Nominal capacity* at 200ppm CaCO ₃ m ³	Typical salt use** per generation kg	Pressure loss bar	Resin volume litres	Salt storage kg	Overall dimensions cm H x W x D
B45	520	4.2	2.2	0.20	12	100	107 x 127 x 44
B100	1120	9.0	4.2	0.30	28	100	108 x 130 x 44
B150	1680	13.5	7.2	0.60	42	100	130 x 130 x 44
B200	2240	18.0	9.5	0.90	56	215	155 x 145 x 60
B250	2800	22.5	11.9	0.90	70	215	140 x 163 x 60
B300	3400	27.3	14.5	1.35	85	215	155 x 165 x 60
B420	4000	38.0	20.4	1.55	120	307	182 x 180 x 70

* Typical values ** Normal standard setting



Options available:

- By-pass
- Hard water blending valves
- Salt level monitor
- Pressure gauges
- Hardness monitor
- Salt storage facilities
- Booster pump units
- Skid mounting
- Noryl valve

Lubron Nederland

Lubron Waterbehandeling B.V.
Mechelaarstraat 38
4903 RE Oosterhout (NB)
Postbus 540, Nederland
Fax: +31 (0)162-459192
www.lubronwaterbehandeling.nl
Tel: +31 (0)162-426931

Lubron België

Tel: +32 (0)3877 1519
Fax: +32 (0)3877 2884
Lubron Belgium B.V.B.A.
Antwerpsesteenweg 124
B-2630 Aartselaar
België

Lubron Deutschland

Lubron Wasseraufbereitung GmbH
Riedstrasse 27
71691 Freiberg am Neckar
Deutschland
Tel: +49 (0)7141 2986130
Fax: +49 (0)7141 2986159
www.lubron.de

Lubron UK

Lubron UK Limited
Lubron House
8 Challenge Way, Hythe Hill
Colchester, Essex CO1 2LY
Tel: +44 (0)1206 866444
Fax: +44 (0)1206 866800
www.lubron.co.uk

